

RECEIVED

By Juvoni Sterling at 10:11 am, Jun 26, 2026

REQUEST FOR BIDDING INTERPRETATION (RFBI)

(Email no later than June 30, 2026, 5:00 p.m.)

To: Juvoni Sterling, Project Director
Department of Forestry and Fire Protection
Technical Services Section (TSS)
Phone: 916-709-0777

Email: Juvoni.Sterling@fire.ca.gov

TSS RFBI No.: 2
Requestor RFBI No.: 1
Request Date: 6/22/2026
From (Bidder): Pacific Overhead Door Service

Contact: Jared Moore
Phone: 8059283772
Fax: _____
Email: jnmoore.pacific@gmail.com

All RFBI's received prior to deadline identified above, and responses from the State will be published on <http://www.caleprocure.ca.gov>. Click on "Start Search." In the event name field, enter the project number and click search. While viewing the Event Details, click on "View Event Package" to view RFBI responses.

Project No.: 3540SRAEUCO0182
Project Name: Parkfield Fire Station Facility Replacement
Location: 70331 Vineyard Canyon Road, Parkfield, California

Drawing Reference: A601 Door Schedule and Type Project Manual Reference: _____

Question: All doors listed on A601 Door Schedule are the same 3' x 7' size. What are the sizes of the type D9 roll-up doors?

The type D9 roll-up doors are 12'-0"x12'-0".

Response by S.Hall

Bidder's Authorized Signature

[X] Check here if additional pages attached

Page 1 of 2

DOOR SCHEDULE																	
DOOR NUMBER	DOOR TYPE	DOOR										FRAME		REMARKS & ABBREV.			
		WIDTH	HEIGHT	THICKNESS	MATERIAL	FINISH	SINGLE	PAIR	CORE INSULATION	RATING	HARDWARE GROUP	MATERIAL	FINISH	WS WD PC	WELDED STEEL IC INSULATED CORE SOLID CORE WOOD POWDER COAT	PT FF ST HM	PAINT FACTORY FINISH STAIN HOLLOW METAL
1	D1	3'-0"	7'-0"	1 3/4"	HM	PC	●	-	IC	N/A	1	WS	PC	1' - 2" SIDELITE			
2	D1	3'-0"	7'-0"	1 3/4"	HM	PC	●	-	IC	N/A	1	WS	PC	1' - 6" SIDELITE			
3	D1	3'-0"	7'-0"	1 3/4"	HM	PC	●	-	IC	N/A	1	WS	PC	2' - 0" SIDELITE			
4	D9	3'-0"	7'-0"	1 3/4"	HM	FF	●	-	IC	N/A	5	HM	FF				
5	D9	3'-0"	7'-0"	1 3/4"	HM	FF	●	-	IC	N/A	5	HM	FF				
6	D4	3'-0"	7'-0"	1 3/4"	HM	PC	●	-	IC	N/A	1	HM	PC				
7	D4	3'-0"	7'-0"	1 3/4"	HM	PC	●	-	IC	N/A	1	HM	PC				
8	D9	3'-0"	7'-0"	1 3/4"	HM	FF	●	-	IC	N/A	5	HM	FF				
9	D9	3'-0"	7'-0"	1 3/4"	HM	FF	●	-	IC	N/A	5	HM	FF				
10	D4	3'-0"	7'-0"	1 3/4"	HM	PC	●	-	IC	N/A	1	HM	PC				
11	D3	3'-0"	7'-0"	1 3/4"	HM	PC	●	-	IC	N/A	1	HM	PC				
12	D1	3'-0"	7'-0"	1 3/4"	HM	PC	●	-	IC	N/A	1	WS	PC	1' - 2" SIDELITE			
13	D5	3'-0"	7'-0"	1 3/4"	HM	PC	●	-	IC	N/A	1	HM	PC				
14	D2	3'-0"	7'-0"	1 3/4"	HM	PC	-	●	IC	N/A	4	HM	PC				
15	D6	3'-0"	7'-0"	1 3/4"	WD	ST	●	-	-	N/A	3	HM	PT				
16	D6	3'-0"	7'-0"	1 3/4"	WD	ST	●	-	-	N/A	3	HM	PT				
17	D6	3'-0"	7'-0"	1 3/4"	WD	ST	●	-	-	N/A	3	HM	PT				
18	D6	3'-0"	7'-0"	1 3/4"	WD	ST	●	-	-	N/A	2	HM	PT				
19	D8	3'-0"	7'-0"	1 3/4"	AL	FF	●	-	-	N/A	2	HM	PT				
20	D3	3'-0"	7'-0"	1 3/4"	WD	ST	●	-	-	N/A	2	HM	PT				
21	D6	3'-0"	7'-0"	1 3/4"	WD	ST	●	-	-	N/A	2	HM	PT				
22	D6	3'-0"	7'-0"	1 3/4"	WD	ST	●	-	-	N/A	2	HM	PT				
23	D6	3'-0"	7'-0"	1 3/4"	WD	ST	●	-	-	N/A	2	HM	PT				
24	D6	3'-0"	7'-0"	1 3/4"	WD	ST	●	-	-	N/A	2	HM	PT				
25	D6	3'-0"	7'-0"	1 3/4"	WD	ST	●	-	-	N/A	2	HM	PT				
26	D6	3'-0"	7'-0"	1 3/4"	WD	ST	●	-	-	N/A	2	HM	PT				
27	D6	3'-0"	7'-0"	1 3/4"	WD	ST	●	-	-	N/A	2	HM	PT				
28	D1	3'-0"	7'-0"	1 3/4"	HM	PT	●	-	-	N/A	3	HM	PT				
29	D6	3'-0"	7'-0"	1 3/4"	WD	ST	●	-	-	N/A	3	HM	PT				
30	D4	3'-0"	7'-0"	1 3/4"	HM	PT	●	-	-	N/A	2	HM	PT				
31	D4	3'-0"	7'-0"	1 3/4"	HM	PT	●	-	-	N/A	2	HM	PT				
32	D6	3'-0"	7'-0"	1 3/4"	HM	PT	●	-	-	N/A	3	HM	PT				
33	D6	3'-0"	7'-0"	1 3/4"	HM	PT	●	-	-	N/A	3	HM	PT				
34	D6	3'-0"	7'-0"	1 3/4"	HM	PT	●	-	-	N/A	3	HM	PT				
35	D4	3'-0"	7'-0"	1 3/4"	HM	PT	●	-	-	N/A	2	HM	PT				
36	D6	3'-0"	7'-0"	1 3/4"	HM	PT	●	-	-	N/A	2	HM	PT	HOLD OPEN FUNCTION ON CLOSER			
37	D4	3'-6"	7'-0"	1 3/4"	HM	PT	●	-	-	N/A	2	HM	PT				
38	D4	3'-0"	7'-0"	1 3/4"	HM	PT	●	-	-	N/A	2	HM	PT				
39	D4	3'-0"	7'-0"	1 3/4"	HM	PT	●	-	-	N/A	2	HM	PT				
40	D4	3'-6"	7'-0"	1 3/4"	HM	PT	●	-	-	N/A	2	HM	PT				
41	D6	3'-0"	7'-0"	1 3/4"	HM	ST	●	-	-	45 MIN.	2	HM	PT	45 MINUTE RATED DOOR AND FRAME			
1P	D7	3'-0"	7'-0"	1 3/4"	HM	PT	-	●	-	N/A	4	HM	PC	PUMP BLDG			
1S	D7	3'-0"	7'-0"	1 3/4"	HM	PT	-	●	-	N/A	4	HM	PC	STORAGE BLDG			
1W	D7	3'-0"	7'-0"	1 3/4"	HM	PT	-	●	-	N/A	4	HM	PC	VEH. WASH BLDG; PROVIDE LOUVERS AT EACH DOOR			
2W	D7	3'-0"	7'-0"	1 3/4"	HM	PT	-	●	-	N/A	4	HM	PC	VEH. WASH BLDG; PROVIDE LOUVERS AT EACH DOOR			

DOOR TYPES

Diagram of D1 Full Vision W/ Sidelite door. Shows a door with a vision panel (T) and a sidelite (T). Dimensions: 36" TYP. for the sidelite, and a note: BOTTOM 10" OF ALL DOORS SHALL HAVE A SMOOTH UNINTERRUPTED SURFACE.

Diagram of D2 Full Vision Pair door. Shows two doors with vision panels (T).

Diagram of D3 Full Vision door. Shows a single door with a vision panel (T).

Diagram of D4 Half Glass door. Shows a door with a half glass panel (T). Dimension: 43" MAX.

Diagram of D5 Louver door. Shows a door with a louver panel.

Diagram of D6 Flush Panel door. Shows a door with a flush panel.

D1
FULL VISION W/
SIDELITE

DOOR W/ VISION PANEL
TEMPERED GLASS

D2
FULL VISION PAIR

DOOR WITH VISION PANEL
TEMPERED GLASS

D3
FULL VISION

DOOR W/ VISION PANEL
TEMPERED GLASS

D4
HALF GLASS

DOOR W/ VISION PANEL
TEMPERED GLASS

D5
LOUVER

-

D6
FLUSH PANEL

-

Diagram of D7 Flush Pair door. Shows two doors with flush panels.

Diagram of D8 Storefront door. Shows a door with a vision panel (T). Dimensions: 1'-6", 3'-0", 1'-6". Note: PROVIDE LOUVERS AT 1W & 2W.

Diagram of D9 Coiling Door. Shows a door with a coiling panel. Dimension: ± 5'-4".

D7
FLUSH PAIR

-

D8
STOREFRONT

DOOR WITH VISION PANEL
TEMPERED GLASS

D9
COILING DOOR

DOOR WITH VISION PANEL
TEMPERED GLASS

NOTE:
SEE SHEET A 500 FOR
ACCESSIBILITY REQUIREMENTS
FOR DOORS

HARDWARE GROUPS

GROUP 1 - MORTISED
1.5 PAIRS OF HINGES
MORTISED LOCKSET
CLOSER WITH LIMITER
THRESHOLD
KICK PLATE
DOOR GASKETS
DOOR BOTTOM

GROUP 2 - PASSAGE
1.5 PAIRS OF HINGES
BORED LATCHSET
CLOSER
DOORSTOP
KICK PLATE
DOOR GASKETS

GROUP 3 - PRIVACY
1.5 PAIRS OF HINGES
BORED LOCKSET
CLOSER
DOORSTOP
KICK PLATE
DOOR GASKETS
COAT HOOK

GROUP 4 - PAIR
3 PAIRS OF HINGES
BORED LOCKSET
MATCHING DUMMY TRIM
FLUSH BOLTS
2 CLOSERS WITH LIMITERS
THRESHOLD
2 KICK PLATES
2 DOOR BOTTOMS
DOOR GASKETS

GROUP 5 - COILING
LOCKSET - MANUFACTURER'S
STANDARD; MATCH BUILDING KEY
SYSTEM AS DIRECTED BY STATE
REPRESENTATIVE

GENERAL DOOR NOTES

1. VERIFY LOCK FUNCTIONS, CYLINDERS AND KEYING WITH THE STATE REPRESENTATIVE.

2. PROVIDE ACCESSIBLE SIGNAGE AT BATHROOMS AND RESTROOMS. SEE SHEET A500. SEE SHEET A102F & A103F FOR OTHER DOOR SIGNAGE / LOCATIONS.

3. PROVIDE INSECT, FLAME AND EMBER INTRUSION PREVENTION SCREENING ON ALL DOOR LOUVERS UNLESS OTHERWISE NOTED.

4. WUI EXTERIOR DOOR ASSEMBLY - EXTERIOR GLAZED DOORS AND EXTERIOR GLAZED OPENINGS WITHIN EXTERIOR DOORS SHALL BE INSULATED GLASS UNITS WITH A MINIMUM OF ONE TEMPERED PANE.

5. FIELD VERIFY ALL OPENINGS.

6. EXTERIOR DOORS AND FRAMES SHALL BE PAINTED TO MATCH EXTERIOR WINDOW COLOR.

7. INSTALL FRAME WITH FASTENERS EXPOSED TO INTERIOR.

8. VEHICLE ACCESS DOORS ARE NOT REQUIRED TO BE RATED.

9. TEMPERED WIRE GLASS TO COMPLY WITH ASTM E119 SECTION 716.2.

10. ALL RATED ASSEMBLIES SHALL BE PROVIDED WITH APPROVED GASKETING MATERIAL AND INSTALLED TO PROVIDE A SEAL WHERE THE DOOR MEETS THE STOP ON BOTH SIDES AND ACROSS THE TOP. DOOR AND FRAME SHALL BEAR AN APPROVED LABEL OR OTHER IDENTIFICATION SHOWING THE RATING THEREOF, FOLLOWED BY THE LETTER "S" PER CBC, NFPA 105 AND 252.

11. FIRE RATED DOOR FRAME SHALL BE INSTALLED STRICTLY PER MANUFACTURER'S PRINTED INSTRUCTIONS AND THE INSTRUCTIONS SHALL BE MADE AVAILABLE TO THE INSPECTING AUTHORITIES PER CBC.

12. THE LEVER OF LEVER-ACTUATED LATCHES OR LOCKS MUST BE CURVED WITH A RETURN TO WITHIN 1/2 INCH OF THE DOOR TO PREVENT CATCHING ON CLOTHING OF PERSONS DURING EGRESS.

13. 11B-309.4 OPERATION. OPERABLE PARTS SHALL BE OPERABLE WITH ONE HAND AND SHALL NOT REQUIRE TIGHT GRASPING, PINCHING, OR TWISTING OF THE WRIST. THE FORCE REQUIRED TO ACTIVATE OPERABLE PARTS SHALL BE 5 POUNDS MAXIMUM.

14. 11B-404.2.7 DOOR AND GATE HARDWARE. HANDLES, PULLS, LATCHES, LOCKS AND OTHER OPERABLE PARTS ON DOORS AND GATES SHALL COMPLY WITH SECTION 11B-309.4. OPERABLE PARTS OF SUCH HARDWARE SHALL BE 34 INCHES MINIMUM AND 44 INCHES MAXIMUM ABOVE THE FINISH FLOOR OR GROUND, WHERE SLIDING DOORS ARE IN FULLY OPEN POSITION, OPERATING HARDWARE SHALL BE EXPOSED AND USABLE FROM BOTH SIDES

15. 1010.1.9 DOOR OPERATIONS. EXCEPT AS SPECIFICALLY PERMITTED BY THIS SECTION, EGRESS DOORS SHALL BE READILY OPERABLE FROM THE EGRESS SIDE WITHOUT THE USE OF A KEY OR SPECIAL KNOWLEDGE OR EFFORT.

16. 11B-404.2.8.1 DOOR CLOSERS AND GATE CLOSERS. DOOR CLOSERS AND GATE CLOSERS SHALL BE ADJUSTED SO THAT FROM AN OPEN POSITION OF 90 DEGREES, THE TIME REQUIRED TO MOVE THE DOOR TO A POSITION OF 12 DEGREES FROM THE LATCH IS 5 SECONDS MINIMUM.

17. 11B-404.2.8.2 SPRING HINGES. DOOR AND GATE SPRING HINGES SHALL BE ADJUSTED SO THAT FROM THE OPEN POSITION OF 70 DEGREES, THE DOOR OR GATE SHALL MOVE TO THE CLOSED POSITION IN 1.5 SECONDS MINIMUM.

18. 11B-404.2.9 DOOR AND GATE OPENING FORCE. THE FORCE FOR PUSHING OR PULLING OPEN A DOOR OR GATE SHALL BE AS FOLLOWED:

a. INTERIOR HINGED DOORS AND GATES: 5 POUNDS MAXIMUM.

b. SLIDING OR FOLDING DOORS: 5 POUNDS MAXIMUM.

c. REQUIRED FIRE DOORS: THE MINIMUM OPENING FORCE ALLOWABLE BY THE APPROPRIATE ADMINISTRATIVE AUTHORITY, NOT TO EXCEED 15 POUNDS.

d. EXTERIOR HINGED DOORS: 5 POUNDS MAXIMUM.

19. GAPS BETWEEN DOORS AND DOOR OPENINGS, AT THE BOTTOM, SIDES AND TOPS OF DOORS SHALL NOT EXCEED 1/8 INCH.

DSA Approval

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 01-121605 INC: 01
REVIEWED FOR
SS ☒ FLS ☐ ACS ☐
DATE: 05/01/2025

OSFM Approval

OFFICE OF THE STATE FIRE MARSHAL
APPROVED FIRE AND PANIC ONLY
06/03/25
24-1668
FIRE
SINCE 1895
Approval of this plan does not authorize or approve any omission or deviation from applicable regulations. Final approval is subject to field inspection. One set of approved plans shall be available on the project site at all times.

PARKFIELD
FIRE STATION
FACILITY
REPLACEMENT
70331 VINEYARD CANYON ROAD
PARKFIELD, CALIFORNIA 93461
MONTEREY COUNTY

1131 S STREET, SACRAMENTO, CA 95811-2460

REVISIONS

NO.	DATE	DESCRIPTION
1		
2		
3		
4		
5		
6		
7		
8		

JOB NUMBER: 2244
DESIGNED BY: A. HOTZ
DRAWN BY: A. HOTZ
REVIEWED BY: D. BAISA
FILE DATE: APR 2025
SHEET TITLE:
DOOR SCHEDULE AND TYPES
SHEET NUMBER
A601

V3